997574

Approved For Belease 2001/11/07: CIA-RDP78B0474ZA0003000300055.076

13 September 1965

Please Reference: A51-65-3345

25X1A

25X1A

U. S. Government

Subject:

4 x 5 Chip Processor

Gentlemen:

a review In co-operation with was made of the 4 x 5 Chip Processor with the objective or evaluating the possibility of employing it as a sensitometric processor for use on Contract

> 25X1A 25X1A

25X1A

A shortened form of step wedge as obtained from an This strip is sensitometer was sent to approximately 5-1/2-inches in length, as against the 9-1/2-inches length of the standard step wedge, and as such, it will be possible to process these shorter step wedges in the 4 x 5 Chip Processor by providing suitable plastic mounting frames.

Other changes required to adapt the processor for sensitometric processing are as follows:

- Increase the temperature control range to 130°F. 1.
- Increase the transport speed to give a minimum 2. developing time of 5 seconds.
- Manufacture plastic mounting frames. 3.

This document contains information affecting the National Defense of the United States within the meaning of the Espionage Law, Title 18, U. S. C., Section 793 and 794. Its transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.

continued - - -

Declass Review by NIMA/DOD

GROUP - 1 Excluded from Automatic Downgrading and declassification

U. S. Government

2

13 September 1965 A51-65-3345

25X1A

I am informed by that if agreement on the adaptation of the Chip Processor as suggested is reached, a saving in time and money will be effected if the changes are made before assembly of the Chip Processor is completed. The changes proposed above will in no way degrade the capability of the Chip Processor to meet specification requirements.

I enclose also a copy of a proposed performance evaluation program for the Chip Processor.

If the above program is approved, the use of an Sensitometer will be required as G. F. E.

25X1A

Please advise at your earliest convenience if this proposal meets with your approval, and whether or not a Sensitometer is available. We will withhold any pricing action pending your comments.

25X1A

Very truly yours,

25X1A



IGR:ml Encl.



PROPOSED 4 x 5 CHIP PROCESSOR PERFORMANCE EVALUATION PROGRAM

September 1965



25X1A

OBJECTIVE

The objective of this program is to establish the photographic and functional performance of the processor.

PHASE 1 - EVALUATE PROCESSOR PERFORMANCE

Preliminary check-out to determine if all electrical, mechanical and plumbing systems are functioning properly.

- Temperature Indicator Accuracy
 Check ready light indicator against actual solution temperatures.
- 2. Solution Temperature Pull-Up Time

 Determine the time required to heat processing solution from ambient temperature to working temperature (predetermined set point).
- 3. Solution Temperature Stabilization
 After solution stabilizes, record temperature to determine set point of heating system.
- 4. Drier Temperature Pull-Up Time

 Determine the time required to elevate the drier temperature to set point of heater system. Record maximum dry box temperature.
- 5. Film Transport System

 Determine the accuracy of the transport system. Record variation.
- 6. Light Tightness
 Visual examination of the film after processing in normal room light.
- 7. Power Consumption
 Check starting and continuous operating electrical loads.
- 8. Check Drain System

PHASE II - PHOTOGRAPHIC QUALITY TESTING

- 1. Film and Exposure

 Check performance of processor to determine its capability of producing an even edge to edge density consistently.
- 2. Replenish System

 Determine the rate of replenisher for both developer and fixer (cc/minute).

Approved For Release 2001/11/07 : CIA-RDP78B047474000300030003-3

- 3. Physical and Photographic Defects on Film
 - A. Scratches

D. Creases

B. Mottling

E. Drying

C. Dust Specks

F. Drying Marks

- 4. Wash Section Determine GPM.
- 5. Archival Quality

Residual thiosulfate content will be determined as per ASA pH 4.8 1958.

- 6. Summary of Performance
- 7. Recommendations as necessary

Determine Proper selection of Jehn-developer containations processing temperatures, speeds, et for highest quality output (resolution, gama